



Product Features:

Item #	Item	Performance
1	IP Grade	IP68
2	Cable Sealing Method	Compressed gel
3	Closure Sealing Method	Hinged with latch
4	Connection Capacity	8-fiber with SC connector, 16-fiber with LC connector
5	Splice Capacity	48 fibers
6	Mounting Method	Wall, Pole, Aerial or Ped with kits

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: LINEAR: ANGULAR:		FINISH:	DEBUR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION
DRAWN: Nick Chen		DATE: 2025/11/11		 TITLE: HyperDrop PAS GEL Compact 8 (TM) (Patch and Splice), IP68, 4 input/2 midspan, 8 output, includes 1 built in splice tray	
CHK'D: Simon Wu		DATE: 2025/11/11			
APP'VD: Xiao Yao		DATE: 2025/11/11			
MATERIAL: PP+GF for outer case ABS for inside parts Stainless Steel for metal parts			WEIGHT: 0.9KG	DWG NO. HyperDrop PAS-Compact 8	A3
				SCALE:1:2	SHEET 1 OF 1