



Product Features:

Item #	Item	Performance
1	IP Grade	IP68
2	Cable Sealing Method	Compressed gel
3	Closure Sealing Method	Hinged with latch
4	Connection Capacity	8-fiber with SC connector, 16-fiber with LC connector
5	Splice Capacity	96 fibers
6	Mounting Method	Wall, Pole, Aerial or Ped with kits

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: TOLERANCES: LINEAR: ANGULAR:		FINISH:	DEBUR AND BREAK SHARP EDGES	DO NOT SCALE DRAWING	REVISION
DRAWN: Nick Chen		DATE: 2025/11/11		 <p>TITLE: HyperDrop PAS GEL 8™ with SC/APC H connectors that are compatible with Optitaps, IP68, 4 input/2 midspan, 16 Optitap and 8 standard outputs, includes 1 built in splice tray.</p>	
CHK'D: Simon Wu		DATE: 2025/11/11			
APP'VD: Xiao Yao		DATE: 2025/11/11			
MATERIAL: PP+GF for outer case ABS for inside parts Stainless Steel for metal parts			WEIGHT: 3.0KG	DWG NO. HyperDrop PAS-8	A3
				SCALE:1:2	SHEET 1 OF 1