



Product Features:

Item #	Item	Performance
1	IP Grade	IP68
2	Cable Sealing Method	Compressed gel
3	Closure Sealing Method	Hinged with latch
4	Connection Capacity	8-fiber with SC connector, 16-fiber with LC connector
5	Splice Capacity	48 fibers
6	Mounting Method	Wall, Pole, Aerial or Ped with kits

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS		FINISH:		DEBUR AND BREAK SHARP EDGES		DO NOT SCALE DRAWING		REVISION	
SURFACE FINISH:									
TOLERANCES: LINEAR: ANGULAR:								TITLE:	
	NAME	DATE				HyperDrop PAS GEL Compact 8™ with SC/APC H connectors that are compatible with Optitaps, IP68, 4 input / 2 midspan, 8 Optitap and 8 standard outputs, 8 simplex 1M pigtaills preinstalled into Optitaps.			
DRAWN	Nick Chen	2025/11/21							
CHK'D	Simon Wu	2025/11/21							
APP'VD	Xiao Yao	2025/11/21							
				MATERIAL: PP+GF for outer case ABS for inside parts Stainless Steel for metal parts		DWG NO.		A3	
				WEIGHT: 1.1KG		SCALE:1:2		SHEET 1 OF 1	